DID YOU KNOW?

about our...

GSL Cone Lock Hex Nut

GSL CONE LOCK HEX NUT 316 STAINLESS / ISO 7042 / LANFRANCO

Part	D	Pitch	H - min.	H - max.	M - min.	S	Е
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
NJ16NGSLM08	M8	1.25	7.14	8.00	5.15	13.00	14.38
NJ16NGSLM10	M10	1.50	8.94	10.00	6.43	16.00	17.77
NJ16NGSLM12	M12	1.75	11.57	12.00	8.30	18.00	20.03
NJ16NGSLM16	M16	2.00	15.70	16.40	11.28	24.00	26.75
NJ16NGSLM20	M20	2.50	19.00	20.30	13.52	30.00	32.95


FEATURES


- Reliable all metal locknut
- Maintains prevailing torque in high temperature applications

APPLICATIONS

- Mining and processing
- · Railways and transportation
- Energy
- Military
- Industrial









Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.





3

hobson.com.au **QUALITY FASTENERS** SINCE 1935





PRODUC