DID YOU KNOW?

about our...






Flat Round Sampson™ Washer

FLAT ROUND SAMPSON™ WASHER

PLAIN / ASTM F436 / 38-45HRC

Part	Size	Outer Diameter	Inner Diameter	Thickness
	(inch)	OD (mm)	ID (mm)	T (mm)
WR43P025	1/4"	16.7	7.5	1.7
WR43P031	5/16"	18.3	9.2	1.7
WR43P037	3/8"	21.5	10.7	1.7
WR43P043	7/16"	24.2	12.3	1.7
WR43P050	1/2"	27.8	13.9	3.5
WR43P056	9/16"	30.9	16.3	3.7
WR43P062	5/8"	34.2	17.9	3.8
WR43P075	3/4"	38.1	21.1	3.8
WR43P087	7/8"	45.3	24.2	4.0
WR43P100	1"	52.4	27.8	4.0
WR43P112	1-1/8"	58.8	31.0	4.0
WR43P125	1-1/4"	65.1	35.7	4.0
WR43P137	1-3/8"	71.5	38.9	4.0
WR43P150	1-1/2"	77.8	42.1	4.0
WR43P162	1-5/8"	82.6	46.5	5.8
WR43P175	1-3/4"	87.3	48.4	5.8
WR43P187	1-7/8"	92.7	52.9	5.8
WR43P200	2"	96.9	54.7	5.8
WR43P225	2-1/4"	103.2	61.1	7.3
WR43P250	2-1/2"	115.9	67.5	7.4
WR43P300	3"	141.3	80.2	7.4





APPLICATIONS

 Hardened washer suitable for use with bolts and set screws up to Grade 8

FEATURES

- Complies with ASTM F436
- 38-45 HRC



Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

