

# Builder's Guide



Hobson stock Metric Class 4.6 UTS Builders Allthread rod and accessories in Zinc Plated, Hobkote® and Hot Dip Galvanised finish. Zinc Plated product conforms to ISO4042 [Fasteners – Electroplated coatings] with 5 micron in thickness. The Hobkote® coating conforms to ISO4042 with between 5-8 micron in thickness and a specially formulated passivation. The Hobkote® coating performs with 33% more corrosion resistance than Zinc Plated product. Hot Dip Galvanised product conforms to AS1214 [Hot-Dip Galvanised Coatings

On Threaded Fasteners] with 42 micron in thickness and Mechanically Galvanised product conforms to ASTM B695 Class 40 [Standard Specification for Coatings of Zinc Mechanically Deposited on Iron and Steel] with 40 micron in thickness. Hobson Galvanised products comply with AS1684 [Residential timber-framed construction – Cyclonic areas] requirement of 40 micron from AS1397 [Steel sheet and strip--Hot-dip zinc-coated or aluminium/zinc-coated] coating class Z275.

Threaded Rod	Hexagon Couplers	Hexagon Nuts	Washers Round and Square	L- Bolts: Foundation Bolts	Xbolts®	Xbolt® Couplers	Z brackets
							

## Galvanised Range

### Products available in HOBKOTE® (M10,M12,M16,M20)

Threaded Rod	Hexagon Couplers	Hexagon Nuts	Washers Round and Square	L- Bolts: Foundation Bolts
				



## Range

Threaded Rod	Hexagon Couplers	Hexagon Nuts	Washers Round and Square
			

## Zinc Plated Z/P Range