

## **Drills and Chisels Chart**

PRODUCT			FEATURES	AVAILABLE SIZES	Reinforced concrete	Concrete	Masonry	Calcium silicate brick	Granite	Marble	Iron	Steel	Wall tiles	Roof tiles	BENEFITS
		MHP-T Hammer Drill Bit, SDS-Plus, 3-cutter		ø 5-16 mm WL: 50-550 mm		<b>②</b>					-	-	-	-	■Hammer drilling ■Particularly powerful and rugged multi-cutter ■Optimum extraction of drill dust promotes high drilling performance ■Recessed carbide tip for extreme resilience in reinforcement steel
		MHP-Y Hammer Drill Bit, SDS-Plus, Y-cutter		ø 18-20 mm WL: 200-550 mm							-	-	-	-	
		MHP-D Hammer Drill Bit, SDS-Plus, 2-cutter		ø 4-26 mm WL: 50-950 mm	<b>⊘</b>				<b>⊘</b>	<b>⊘</b>	-	-	-	-	■Hammer drilling ■Optimum extraction of drill dust promotes high drilling performance ■Recessed carbide tip for extreme resilience in reinforcement steel
		MHX-T Hammer Drill Bit, SDS-Max, 3-cutter		ø 12-16 mm WL: 200-800 mm							-	-	-	-	■Hammer drilling ■Particularly powerful and rugged multi-cutter
2010000		MHX-Y Hammer Drill Bit, SDS-Max, Y-cutter		ø 18-45 mm WL: 200-1200 mm	<b>②</b>						-	-	-	-	Optimum extraction of drill dust promotes high drilling performance     Recessed carbide tip for extreme resilience in reinforcement steel
•		MHP-Clean Hollow Drill Bit, SDS-Plus, 2-cutter		ø 8-18 mm WL: 150-250 mm			<b>②</b>		<b>&gt;</b>	<b>⊘</b>	-	-	-	-	■Hammer drilling ■Innovative 2-in-1 drill bit: drilling and dust extraction in a single ste
		MHX-Clean Hollow Drill Bit, SDS-Max, Y-cutter		ø 18-35 mm WL: 400 mm			<b>②</b>	0	<b>&gt;</b>	<b>⊘</b>	-	-	-	-	Particularly suitable for setting chemical anchors Saves cleaning of the surroundings and drill hole
		MSZ Drill Bit, cylindrical		ø 3-20 mm WL: 45-350 mm	-	<b>⊘</b>			<b>∂</b>	<b>⊘</b>	-	-	-	-	■Impact drilling ■High durability even in the hardest materials ■Fast drilling speed
	\$	MDZ Allmat Drill Bit, cylindrical		ø 5-14 mm WL: 50-310 mm	-	<b>⊘</b>	<b>⊘</b>		<b>⊘</b>		-	-	<b>⊘</b>	<b>⊘</b>	■Rotary drilling, impact drilling ■Performant, resistant and accurate ■Easy drilling also in smooth and hard surfaces
		MMP SDS-Plus Chisel		L: 250 mm	-						-	-	-	-	■For all popular applications ■Effortless chiseling and faster penetration ■Anti-lock
		MMX SDS-Max Chisel		L: 175-600 mm	-						-	-	-	-	■For the toughest tasks ■Effortless chiseling and faster penetration ■Anti-lock
	6	HSS Drill Bit, cylindrical		ø2,5-16 mm WL: 30-120 mm	-	-	-	-   -	-	- (			-	-	■For metal solutions ■Ideal for unalloyed steels ■Long life
	F	HSS-D Drill Bit, double sided, cylindrical		ø 3,2-5,2 mm WL: 11-17 mm	-	-	-		-	- (			-	-	■Quick change possible due to double end ■For metal solutions ■Ideal for unalloyed steels
The state of the s	6	MFB Diamond Drill Bit, M14		ø 6-20 mm WL: 12 mm	-	-	-	-   -	-	-	-	-			■Easy drilling also in smooth and hard surfaces ■Clean and accurate holes ■Simple and speedy working

ONLINE ...

FREE Design software download: hobson.com.au/mungo-software

WL=Working length





