

uvex Hearing Protection System

Banded Ear Plugs

uvex xact-band

- AS/NZS 1270:2002 approved
 - SLC80 22dB
 - Class 4
- Pin supported polyurethane banded ear plug
- For industrial use in environments up to 105dB
 - assuming a 85dB criterion



uvex Point of Difference	Benefits
Unique oval shape and ergonomically designed pins with thumb supports for the left and right ear.	Comfortable, hygienic fit following the natural line of the ear canal - no direct contact with the plug during fitting.
Flexible sound absorbers integrated into the band.	Excellent balance of attenuation and safe communication by minimising the risk of isolation (Class 4, SLC80 22dB).
Economical and environmentally friendly.	PVC free band with replaceable sealed soft PUR pods to minimise dirt pick-up and waste.

Target Applications (but not limited to):

- Engineering
- Airlines / cabin crews
- Entertainment industry
- Emergency services
- Fabrication (under welding helmet)

Attenuation data:

Frequency in Hertz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
Mean	25.7	21.4	23.7	25.5	32.5	39.1	37.3
STD. Deviation	5.8	5.5	6.8	7.0	7.3	9.8	8.7
Mean minus SD	19.8	15.9	16.9	18.5	25.2	29.3	28.6

Part Numbers & Packaging:

- 2125.372 - uvex xact-band earband, 5 pieces per box
- XA-RP - replacement pods 1 box 250 pods (5 pairs per mini box)
- AC-BT - portable ear plug holder (1 box, 50 units)

Barcodes:

- 2125.372 - 4031101597577
- XA-RP - 4031101499260
- AC-BT - 4031101268972