

Hearing protection Earmuffs



uvex K20 (page 1 of 2)

- Earmuffs with padded foldable headband with memory foam for optimal wearing comfort
- Continuous length adjustment for an ideal wearing position
- Sealing cushion made of memory foam for good sealing and comfort
- Replaceable sealing cushions for high hygiene standards
- Approved to AS/NZS 1270:2002 - SLC80:30dB, Class 5

SLC80
dB
30



Part Number/Barcode:

- 2630020 - uvex K20 foldable earmuff, black/yellow, SLC80:30dB, Class 5
- Barcode - 4031101928821

Packaging:

- 1 unit per box
- 20 units per carton

Accessories:

- 2599.972 - uvex hygiene kit - 2 sealing cushions, 2 noise insulating foam pads
- AC-EB - uvex earmuff bag with belt loop and hook and loop fastener, black



2599.972



AC-EB

Hearing protection Earmuffs

uvex K20 (page 2 of 2)

Product Details							
Colour	Black/Yellow						
Part No.	2630020						
Design	With foldable headband						
SLC ₈₀	30 dB, Class 5						
Clamping force:	11.1N, 10.7N, 10.7N						
Weight	230g						
Packing	1 unit						
Storage	Storage location, in original packaging, dry, clean, protected from light, UV and heat. UV and heat protected in the temperature range -10° to 55 °C, humidity max. 85%. Storage period 5 years, from date of manufacture. (Date of manufacture see product or packaging) Make sure that during storage the stirrup is not stretched, and the sealing pads are not compressed.						
Life Expectancy of Product	Service life 5 years, from date of manufacture. Recommendation: Regular replacement of the sealing pads extends the service life. Dispose of the product after expiry or immediately if it is damaged or can no longer be cleaned.						
Certified standards							
AS / NZ Standards	AS/NZS 1270:2002						
European Standard	EN 352-1:2020						
American Standard	ANSI S-3.19-1974						
Attenuation Data							
Frequency in Hertz	125	250	500	1000	2000	4000	8000
Mean att. dB	16.2	20.4	30.6	40.1	36.5	35.8	36.7
Std. dev. dB	4.5	4.4	5.3	4.5	3.9	4.4	4.0
APV	11.7	16.0	25.3	35.6	32.6	31.4	32.7

Freq. - frequency
Mean att. - mean attenuation
Std. dev. - standard deviation
APV - assumed protection value

- Hearing protector Class 5 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to **110dB(A)** assuming an **85 dB(A)** criterion. A lower criterion may require a higher protector class.

UVEX SAFETY AUSTRALIA LIMITED PARTNERSHIP

Unit 3 Riverside Centre, 24-28 River Road West, Parramatta NSW 2150, Australia
T 1800 815 790 E info@uvex.com.au
uvex-safety.com.au

UVEX Safety New Zealand Ltd

T +64 800 698 839 E info@uvex.co.nz
uvex-safety.co.nz



CLICK HERE or
SCAN QR code
for more information on
uvex hearing range