

COBRA TPR

FOR CLEAN ENVIRONMENTS AND EXTREME CONDITIONS

The essential all rounder with a panoramic visual field, COBRA TPR offers 180° vision and perfect optical quality. With its built-in TPR seal, this model is especially suitable for clean industries and the agro-food industry. Available with nylon and neoprene strap.

 PLATINUM®



1667001 • Clear with Neoprene Strap




1667101 • Clear



1667102 • Smoke






34g

- +  PLATINUM® () COATING
- + COMPACT, LIGHTWEIGHT AND PANORAMIC
- + TPR SEAL FOR COMFORT
- + 100% SEALED
- + HIGH STRENGTH GOGGLES

bolle
SAFETY

COBRA TPR

FOR CLEAN ENVIRONMENTS AND EXTREME CONDITIONS

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
COBRA TPR	 Clear with Neoprene Strap	1667001	IO & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/ P
	 Clear	1667101	IO & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/ P
	 Smoke	1667102	II & P	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/ P

LENS MARKING

- P**. Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m²) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.
- I**. The letter 'I' signifies 'Medium Impact' approval.
- O**. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

Ocular lens category:

- O**. Range of luminous transmittance 80–100% (Clear).
- 3**. Range of luminous transmittance 8–18% (Smoke).

FRAME MARKING

AS/NZS 1337.1:2010 Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

APPLICATIONS

- Cutting
- Spraying
- Dust protection

MAIN MARKETS

- Construction
- Manufacturing
- Paint
- Automotive

LENSES

- Platinum Coating - A high performance anti-fog + anti-scratch coating system applied on both sides of Clear and Smoke lenses
- 2mm polycarbonate
- 9 base curve
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	Non Applicable
STRAP	15mm adjustable
FOAM	TPR
SPARE LENSES	No

TECHNOLOGIES



The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.



Non-contractual pictures

17/03/2020

Bollé Safety AU Pty Limited
32–40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

Hong Kong Bollé Safety
818, 8/F, Ocean Centre, Harbour City,
5 Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
T.: +852 2732 5038

bollesafety.com.au

bolle
SAFETY