

PILOT 2

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

Pilot 2's co-injected, ventilated frame guarantees unequalled adaptability and comfort.

 PLATINUM




89 g



1679110 • Platinum Clear Lens • Indirect Vented



1679112 • Platinum Smoke Lens • Indirect Vented



1679118 • Platinum CSP Lens • Indirect Vented



1689110 • Platinum Clear Lens • Top Vent Closed



1689112 • Platinum Smoke Lens • Top Vent Closed



1689118 • Platinum CSP Lens • Top Vent Closed







- +  PLATINUM COATING (ATIF)
- + EXCELLENT FIELD OF VISION
- + PP/TPR TWIN/MATERIAL FRAME

- + ADJUSTABLE STRAP
- + FITS OVER PRESCRIPTION GLASSES

bolle
SAFETY

PILOT 2

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

| MODEL | VERSIONS | PRODUCT CODE | LENS MARKING | FRAME MARKING | COATINGS |
|---------|---|--------------|--------------|--------------------|----------------------------|
| PILOT 2 |  Clear - Indirect Vented | 1679110 | CIO | AS/NZS 1337.1.2010 | Anti-scratch/Anti-fog (†P) |
| |  Smoke - Indirect Vented | 1679112 | CI3 | AS/NZS 1337.1.2010 | Anti-scratch/Anti-fog (†P) |
| |  bcsp - Indirect Vented | 1679118 | CI1 | AS/NZS 1337.1.2010 | Anti-scratch/Anti-fog (†P) |
| |  Clear - Top Vent Closed | 1689110 | CIO | AS/NZS 1337.1.2010 | Anti-scratch/Anti-fog (†P) |
| |  Smoke - Top Vent Closed | 1689112 | CI3 | AS/NZS 1337.1.2010 | Anti-scratch/Anti-fog (†P) |
| |  bcsp - Top Vent Closed | 1689118 | CI1 | AS/NZS 1337.1.2010 | Anti-scratch/Anti-fog (†P) |

LENS MARKING

†P Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

I. The letter 'I' signifies 'Medium Impact' approval.

O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

CSP. Recommended for outdoor use in all conditions. CSP technology filters blue light and is combined with the exclusive PLATINUM coating, to sustainably combat fogging and provide permanent visual comfort from a single pair of glasses.

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 - 88% (CSP).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Chemical splash protection
- Spraying
- Acid and alkaline handling
- Wood and metal work
- Cutting
- Dust protection

MAIN MARKETS

- Petro Chemical
- Manufacturing
- Automotive
- Construction
- Paint
- Labs

LENSES

- Platinum Coating - a high performance anti-fog + anti-scratch coating system applied on both sides of Clear, Smoke and **bcsp** lenses
- 100% UV 385 - Clear
- 100% UV 400 - Smoke & **bcsp**

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS

| | |
|--------------|-----------------------|
| LENSES | PC - 2,1 mm - Curve 6 |
| FRAME | PP + TPR |
| TEMPLES | Non Applicable |
| STRAP | Nylon |
| FOAM | No |
| SPARE LENSES | No |

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact and chemical splash protection. Resists a 6mm at 45 m/s.