

VAPOUR DUO

PREMIUM GOGGLE, HIGHLY RESISTANT TO FOG

Vapour Duo has twin equalisers which remove moisture from between the front and back lenses whilst balancing the inner goggle temperature and pressure.



Clear Frame With SBR Foam
/ Dual Clear Lens / Indirect
Lower Vents • 1650410



Smoke Frame With SBR Foam
/ Dual Smoke Lens / Indirect
Lower Vents • 1650408



96g

ACCESSORIES



- 1650411 • Clear Duo Lens
Only with Equaliser
- 1650412 • Smoke Duo Lens
Only with Equaliser

- + LOW PROFILE, LIGHTWEIGHT TPR FRAME**
- + DOUBLE LENS: AF/AS LENS, 3.0MM PC OUTER LENS, ANTI FOG INNER LENS AND TWIN EQUALISERS**
- + LARGE ADJUSTABLE STRAP**
- + REPLACEMENT CLEAR AND SMOKE LENS OPTIONS**
- + SPLASH APPROVED**

bollé
SAFETY

VAPOUR DUO

PREMIUM GOGGLE, HIGHLY RESISTANT TO FOG

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
VAPOUR DUO	 Clear Frame Clear Duo Lens Close Cell Foam Indirect Lower Vents, Equaliser	1650410	CIO	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog
	 Smoke Frame Smoke Duo Lens Close Cell Foam Indirect Lower vents, Equaliser	1650408	CI3	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog

LENS MARKING

- C.** The letter 'C' signifies that the product has been tested and approved for use against splashes and is appropriate for chemical handling.
- I.** The letter 'I' signifies 'Medium Impact' approval.
- O.** The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O.** Range of luminous transmittance 80-100% (clear).
- 3.** Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Chemical splash protection
- Dust protection
- Spraying
- Acid and alkaline handling
- Engineering
- Milling
- Process work

MAIN MARKETS

- Petrochemical industry
- Mining
- Construction
- Paint
- Manufacturing

LENSES

- ALS' anti-fog/anti-scratch outer lens, anti-fog inner lens
- 99.9% UV 385 - Clear
- 99.9% UV 400 - Smoke

FRAME MARKING

AS/NZS 1337.1:2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS	
LENSES	PC 3.0mm (outside)
FRAME	TPR
TEMPLES	Non applicable
STRAP	Yes
FOAM	Yes
SPARE LENSES	No

ASIA/PACIFIC HEADQUARTERS:

Bollé Safety AU Pty Limited
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

bollesafety.com.au

NEW ZEALAND:

T.: 0800 2655 369
E: bolle@bolle.co.nz

bolle
SAFETY