

BL20

B-LINE is a range of safety eyewear **adapted** to the most common industrial risks. **B-LINE** benefits from Bollé Safety's expertise and quality.

BL20 provides **full head and face protection** and a wide field of vision. Adjustable headband and protective headgear.

b LINE



BL20PI



BL20FAPI





260 g

- + WIDE FIELD OF VISION
- + FULL HEAD AND FACE PROTECTION
- + ADJUSTABLE HEADBAND
- + HIGH IMPACT PROTECTION

bollé
SAFETY

BL20

MODEL	REFERENCES	LENS MARKING			FRAME MARKING			COATINGS
		EN166	ANSI	AS/NZS	EN166	ANSI	AS/NZS	
BL20	 BL20PI	☞ 1BT ☹	☞ Z87+U6	☞ BO	☞ EN166 3 BT	☞ Z87+ D3 CSA Z94.3	AS/NZS 1337.1:2010 Lic SMK41061	Anti-scratch
	 BL20FAPI	☞ 1BT ☹	☞ Z87+U6	☞ BO	-	-	-	-

LENS MARKINGS

EN 166

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

ANSI

Z87+ : Impact rated for Plano product - tested and approved to ANSI Z81.1-2015

AS/NZS

Optical class symbols:

O. Range of luminous transmittance 80-100% (clear)

Mechanical strength symbols:

B. High impact, resists a 6 mm, 0.86 g ball at 120 m/s

O. The letter «O» signifies that the product has been approved for the use both outdoors and indoors.

Others symbols:

☹ European standard ☞ Manufacturer name

FRAME MARKINGS

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Z87+ : Impact rated for Plano product - tested and approved to ANSI Z81.1-2015

D3: Splash/droplet protection

AS/NZS 1337.1:2010 : Tested & approved to AS/NZS 1337.1.2010 for high impact protection. Resists a 6 mm, 0.86 g ball at 120 m/s.

Others symbols:

☹ European standard ☞ Manufacturer name

Bollé Safety product approval certificates to standards will be sent on request.

PACKAGING AND EAN13 CODE

	BL20PI	BL20FAPI
Individual packaging	3660740003173	3660740003180
10 spare lens per inner box	-	3660740103187
25 sets (or 200 pcs) per outer pack	3660740203177	3660740203184

BL20PI: 255x305x130mm
Outer pack: 60x51.5x38.5cm // 7.8kg

BL20FAPI: 203x393x1.0mm
Inner box: 20.3x39.3x10cm // 1kg
Outer pack: 46x38.5x29.5cm // 21kg

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



Non-contractual pictures

02/07/2021

EMEA
Bollé Safety
34 rue de la Soie
69100 Villeurbanne
France

U.S.A
Bollé Safety
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
USA

APAC
Bollé Safety AU Pty Limited
32-40 Fairchild St
Heatherton VIC 3202
Australia

HONG KONG
Bollé Safety
818 8/F Ocean Centre
Harbour City 5 Canton Rd
TST Kln Hong Kong

JAPAN
Bolle Brands Japan Limited
4F 2-21-2
Yushima Bunkyo-ku Tokyo
113-0034 Japan

bollesafety.com.au

bolle
SAFETY