

STRAIGHT QUICK CONNECTORS

Features & Benefits

- Non-metallic straight connector for Liquid Tight conduit, halogen free PA6 nylon, extreme low fire hazard UL94 V-0
- Halogen, phosphor and cadmium free, UV resistant
- Temperature rating -40 to +115 degrees, flame retardant
- Self-extinguishing, IP66 RoHS compliant and anti-static
- Self locking push fit installation onto conduit, no tool required



Compliance & Safety

UL 94, the Standard for Safety of Flammability of Plastic Materials for Parts in Devices and Appliance testing, is a plastics flammability standard released by Underwriters Laboratories of the United States. The standard determines the material's tendency to either extinguish or spread the flame once the specimen has been ignited. UL-94 is now harmonized with IEC 60707, 60695,-11-10 and 60695-11-20 and ISO 9772 and 9773.

- **V-0:** Burning stops within 10 seconds on a vertical specimen; drips of particles allowed as long as they are not inflamed
- **V-2:** Burning stops within 30 seconds on a vertical specimen; drips of particles allowed

Ordering Information

PART NUMBER	DESCRIPTION
CFM1-16B	Straight Quick Connector 16mm M12
CFM1-20B	Straight Quick Connector 20mm M20
CFM1-25B	Straight Quick Connector 25mm M25
CFM1-32B	Straight Quick Connector 32mm M32
CFM1-40B	Straight Quick Connector 40mm M40
CFM1-50B	Straight Quick Connector 50mm M50

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.