

NYLON 90 DEGREE CONNECTOR IP66

Features & Benefits

- Non-metallic 90 Degree connector for liquid tight conduit, halogen free PA6 nylon, extreme low fire hazard UL94 V-0
- Halogen, phosphor and cadmium free, UV resistant
- Temperature rating -40 to +115 degrees Celsius, flame retardant
- Self-extinguishing, IP66, anti-static and RoHS compliant
- Self-locking Push Fit installation onto conduit, no tool required



Ordering Information IP66

PART NUMBER	DESCRIPTION
CFM2-10B	90 DEG QUICK CONN 10MM
CFM2-12B	90 DEG QUICK CONN 12MM
CFM2-16B	90 DEG QUICK CONN 16MM
CFM2-20B	90 DEG QUICK CONN 20MM
CFM2-25B	90 DEG QUICK CONN 25MM
CFM2-32B	90 DEG QUICK CONN 32MM
CFM2-40B	90 DEG QUICK CONN 40MM
CFM2-50B	90 DEG QUICK CONN 50MM

Features & Benefits

- IP68 Non-metallic 90 Degree connector for liquid tight conduit, halogen free PA6 nylon, extreme low fire hazard UL94 V-0
- Halogen, phosphor and cadmium free, UV resistant
- Temperature rating -40 to +115 degrees Celsius, flame retardant
- Self-extinguishing, Anti-Static and RoHS compliant
- Self-locking Push Fit installation onto conduit, no tool required

Ordering Information IP68

PART NUMBER	DESCRIPTION
PCM-2M12	IP68 90 DEG QUICK CONN 12MM
PCM-2M16	IP68 90 DEG QUICK CONN 16MM
PCM-2M20	IP68 90 DEG QUICK CONN 20MM
PCM-2M25	IP68 90 DEG QUICK CONN 25MM
PCM-2M32	IP68 90 DEG QUICK CONN 32MM

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.