

# **PRODUCT** DATASHEET

## **K03C-5D RATCHET CRIMP TOOL KIT WITH COMBINATION DIES**

The K03C- 5D is a hand, ratchet terminal crimp tool kit containing a crimping tool frame and five dies. The dies can be changed using an allen key to remove and fasten the die screws on the frame. The dies supplied crimp pre-insulated terminals, indent crimp for uninsulated terminal boot lace ferrules and brass roll crimp terminals.

#### **FEATURES**

- Hand crimping tool frame with five terminal dies
- Ratchet operation ensures correct crimp and reduced hand effort
- Dies for pre-insulated, uninsulated, bootlace ferrules and roll crimp terminals

#### **TERMINAL DIES**

- Pre-insulated terminals red, blue and yellow
- Uninsulated terminals 1.5 to 10 mm<sup>2</sup>
- Bootlace Ferrules die size 04 for 0.5mm<sup>2</sup> to 4 mm<sup>2</sup>
- Bootlace Ferrules die size 16 for 6mm<sup>2</sup> to 16mm<sup>2</sup>
- Roll crimp Terminals 0.5mm<sup>2</sup> to 6 mm<sup>2</sup>

### **ORDERING INFORMATION**

Length: 230mm Weight (Tool & 1 Die Set): 0.6kg

PART NO.	DESCRIPTION
K03C-5D	Terminal Crimper Kit With 5 Dies
INTERCHANGEABLE DIES ARE AVAILABLE TO PURCHASE	
LY-03C	Pre-insulated 0.5-6mm <sup>2</sup>
LY-04C	Pre-insulated 0.14-6mm <sup>2</sup>
LY-10	Un-insulated and lugs 1.5-8mm <sup>2</sup>
LY-03B	Roll crimp open barrel 0.5-6mm <sup>2</sup>
LY-04WF	Bootlace Ferrule 0.5-4mm <sup>2</sup>
LY-06WF	Bootlace Ferrule 0.75-6mm <sup>2</sup>
LY-16WF	Bootlace Ferrule 6-16mm <sup>2</sup>
LY-35WF	Bootlace Ferrule 16-35mm <sup>2</sup>
LY-50WF	Bootlace Ferrule 25-50mm <sup>2</sup>



In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

