



*suttontools*

## T910 -Straight Flute Tap Sets - 8UN -Sutton Tools

---

### Features:

- General purpose use
- Suitable for materials up to 1000N/mm<sup>2</sup>
- Through & blind holes
- Suitable for both hand and machine operations
- Depths up to approx. 1 x d1

### Specifications:

<b>Designation:</b>	N
<b>Material:</b>	HSS
<b>Finish:</b>	Brt
<b>Max Cut Depth:</b>	1xD
<b>Shank Form:</b>	A
<b>Standard:</b>	ISO529
<b>Thread Form:</b>	8UN
<b>Nut Tolerance:</b>	GH8 / 2B
<b>Lead:</b>	Set

Range:

Item #	d1	Limit	Length l1 (mm)	Length l2 (mm)	Diameter d2 (mm)	sq	Length l4 (mm)	z
T9102858	1 1/8	GH8 / 2B	138	48	20	16	20	4
T9103175	1 1/4	GH8 / 2B	151	51	22.4	18	22	4
T9103493	1 3/8	GH8 / 2B	162	57	25	20	24	4
T9103810	1 1/2	GH8 / 2B	170	60	28	22.4	26	4
T9104128	1 5/8	GH8 / 2B	170	60	28	22.4	26	4
T9104445	1 3/4	GH8 / 2B	187	67	31.5	25	28	4
T9104763	1 7/8	GH8 / 2B	187	67	31.5	25	28	4
T9105080	2	GH8 / 2B	200	70	35.5	28	31	4

### Applications:

ISO	VDI	Description	Condition	Hardness	Strength	Optimal
P	1	Steel - Non-alloy, cast & free cutting (~ 0.15 %C)	Annealed	125MPa	440MPa	●
P	2	Steel - Non-alloy, cast & free cutting (~ 0.45 %C)	Annealed	190MPa	640MPa	●
P	3	Steel - Non-alloy, cast & free cutting (~ 0.45 %C)	Quenched & Tempered	250MPa	840MPa	●
P	4	Steel - Non-alloy, cast & free cutting (~ 0.75 %C)	Annealed	270MPa	910MPa	●
P	5	Steel - Non-alloy, cast & free cutting (~ 0.75 %C)	Quenched & Tempered	300HB	1010MPa	
P	6	Steel - Low alloy & cast < 5% of alloying elements	Annealed	180MPa	610MPa	●
P	7	Steel - Low alloy & cast < 5% of alloying elements	Quenched & Tempered	275MPa	930MPa	○
P	8	Steel - Low alloy & cast < 5% of alloying elements	Quenched & Tempered	300HB	1010MPa	
P	9	Steel - Low alloy & cast < 5% of alloying elements	Quenched & Tempered	350HB	1180MPa	
P	10	Steel - High alloy, cast & tool	Annealed	200HB	680MPa	
P	11	Steel - High alloy, cast & tool	Hardened & Tempered	325HB	1100MPa	
P	12	Steel - Corrosion resistant & cast - Ferritic / Martensitic	Annealed	200HB	680MPa	
P	13	Steel - Corrosion resistant & cast - Martensitic	Quenched & Tempered	240HB	810MPa	
M	14.1	Stainless Steel - Austenitic	Age Hardened	180HB	610MPa	
M	14.2	Stainless Steel - Duplex		250HB	840MPa	
M	14.3	Stainless Steel - Precipitation Hardening		250HB	840MPa	
K	15	Cast Iron, Grey (GG) - Ferritic / Pearlitic		180MPa	610MPa	○
K	16	Cast Iron, Grey (GG) - Pearlitic		260HB	880MPa	
K	17	Cast Iron, Nodular (GGG) - Ferritic		160MPa	570MPa	○
K	18	Cast Iron, Nodular (GGG) - Pearlitic		250HB	840MPa	
K	19	Cast Iron, Malleable - Ferritic		130MPa	460MPa	○
K	20	Cast Iron, Malleable - Pearlitic		230HB	780MPa	
N	21	Aluminum & Magnesium, wrought alloy - Non Heat Treatable		60MPa	210MPa	○
N	22	Aluminum & Magnesium, wrought alloy - Heat Treatable	Age Hardened	100MPa	360MPa	○
N	23	Aluminum & Magnesium, cast alloy ?12% Si - Non Heat Treatable		75MPa	270MPa	○
N	24	Aluminum & Magnesium, cast alloy ?12% Si - Heat Treatable	Age Hardened	90MPa	320MPa	○
N	25	Aluminum & Magnesium, cast alloy >12% Si - Non Heat Treatabl		130HB	460MPa	
N	26	Copper & Copper alloys (Brass/Bronze) - Free cutting, Pb > 1%		110MPa	390MPa	○
N	27	Copper & Copper alloys (Brass/Bronze) - Brass (CuZn, CuSnZn)		90HB	320MPa	
N	28	Copper & Copper alloys (Brass/Bronze) - Bronze (CuSn)		100MPa	360MPa	○
N	29	Non-metallic - Thermosetting & fiber-reinforced plastics				
N	30	Non-metallic - Hard rubber, wood etc.				
S	31	High temperature alloys - Fe based	Annealed	200HB	680MPa	
S	32	High temperature alloys - Fe based	Age Hardened	280HB	950MPa	
S	33	High temperature alloys - Ni / Co based	Annealed	250HB	840MPa	
S	34	High temperature alloys - Ni / Co based	Age Hardened	350HB	1180MPa	
S	35	High temperature alloys - Ni / Co based	Cast	320HB	1080MPa	
S	36	Titanium & Titanium alloys - CP Titanium			400MPa	
S	37.1	Titanium & Titanium alloys - Alpha alloys			860MPa	
S	37.2	Titanium & Titanium alloys - Alpha / Beta alloys	Annealed		960MPa	
S	37.3	Titanium & Titanium alloys - Alpha / Beta alloys	Age Hardened		1170MPa	
S	37.4	Titanium & Titanium alloys - Beta alloys	Annealed		830MPa	
S	37.5	Titanium & Titanium alloys - Beta alloys	Age Hardened		1400MPa	
H	38.1	Hardened steel	Hardened & Tempered	45HRC		
H	38.2	Hardened steel	Hardened & Tempered	55HRC		

#### KEY

● Optimal ○ Effective | **P** Steel **M** Stainless **K** Cast Iron **N** Non-Ferous Metals **S** Titanium & Super Alloys **H** Hard Materials

### Applications:

ISO	VDI	Description	Condition	Hardness	Strength	Optimal
H	39.1	Hardened steel	Hardened & Tempered	58HRC		
H	39.2	Hardened steel	Hardened & Tempered	62HRC		
H	40	Cast Iron - Chilled	Cast	400HB	1350MPa	
H	41	Cast Iron	Hardened & Tempered	55HRC		

### KEY

Optimal
  Effective
  P Steel
  M Stainless
  K Cast Iron
  N Non-Ferrous Metals
  S Titanium & Super Alloys
  H Hard Materials